

# Vega chain actuator



- Highest performance in minimum size: the die-cast aluminium casing has a very small section (45 x 32mm) and can be easily built-in in to the frame of curtain walls.
- New concept double link chain completely in stainless steel.
- Chain exit in central position.
- Quick and easy installation: the manual closing position regulation is not required, avoiding possible mistake.  
The stop in closing position is regulated by an electronic limit switch.
- Electronic stop in the intermediate positions in case of overload.
- Supplied with 1.5m cable and pivoting brackets.
- The installation without brackets is possible for windows with pivoting hinges only if the vent height is at least 900mm.
- Available on request a coupling control box for two actuators 24Vdc on the same window.

	<b>VEGA AC</b>	<b>VEGA DC</b>	<b>VEGA IR</b>
VOLTAGE SUPPLY	100Vac – 240 Vac	24Vdc ± 10%	24Vdc/dc ± 10%
ELECTRONIC CONNECTION	3 wires + earth	2 wires	5 wires + 3 for the rain sensor
OPERATION		by polarity inversion	
STROKE	300mm	300mm	300mm
FORCE (push and pull action)	250 N	250 N	250 N
SPEED	~9 mm/s	~9 mm/s	~9 mm/s
CURRENT ABSORPTION (with max load)	0,3 A – 0,15 A	0,7 A	0,7 A
PARALLEL CONNECTION	YES	YES	YES
LIMIT STOP	Electronic	Electronic	Electronic
SAFETY STOP	Electronic	Electronic	Electronic
TIME RATING	50%	50%	50%
PROTECTION CLASS	IP 30	IP 30	IP 30
			Integrated IR RECEIVER Direct connection at the Rain sensor (optional)

<b>PART No.</b>				
GREY	RAL 9006	40900K	40903N	40906Q
BLACK	RAL 9005	40901L	40904O	40907R
WHITE	RAL 9010	40902M	40905P	40908S